SITE-SURVEY PLAN

for the

RAMP

ASCAN PROJECT

September 10, 1993

Prepared for the

United States Department of Defense

Distribution authorized to

U. S. Govt. Agencies Only Other requests shall be referred to:

PROPRIETARY INFORMATION

VA 22060

Submitted by ManTech Services Corporation West Virginia Division 1313 Locust Avenue Fairmont, West Virginia

In support of Contract N00421-91-C-0206



March 3, 1999

Defense Technology Information Center (DTIC)

ATTN: Mr. Jack Rike

8725 John J. Kingman Road, Suite 944

Ft. Belvoir, VA 22060

The Rapid Acquisition of Manufactured Parts (RAMP) program documentation was developed under a series of DoD contracts from the years 1985 – 1998. Under these contracts this program documentation was delivered under numerous FAR data rights clauses which allows for universal distribution to United States Government Agencies only. Many of the individual documents come with contractor "limited rights" statements. These documents will require prior approval of the developing contractor for release to the public.

The RAMP Program documentation's controlling agency transferred from the U.S. Navy to the Defense Logistics Agency (DLA) October 1, 1998. DLA's RAMP Program point of contact is Mr. Don O'Brien, Chief, Technical Enterprise Team, Defense Logistics Support Center, 8725 John J. Kingman Rd., Suite 3135, Ft. Belvoir, VA 22060. Mr. O'Brien may be reached at (703) 767-1414.

Gregory J. Mackmin Systems Analyst

Table of Contents

1	OVERVIEW	1
1	1.1 Required Personnel	
	1.2 Site-Survey Agenda	
_		
	ASCAN SYSTEM REQUIREMENTS	
3	GOVERNMENT-FURNISHED EQUIPMENT (GFE) GENERAL REQUIREMENTS	
	3.1 Space Requirements	3
	3.2 Electrical Requirements	3
4	ENVIRONMENTAL REQUIREMENTS	
	SITE-SURVEY CHECKLIST	

1 OVERVIEW

This plan is published to aid the Naval Surface Warfare Center (NSWC) in identifying the facilities, equipment, and environment required to receive and operate the Advanced Schematic-Capture Automation, Navy (ASCAN) system and all associated Government-furnished equipment (GFE). This plan identifies how the site survey will be performed, and will be used as a guide to perform the actual site survey prior to Navy acceptance and shipment of the ASCAN system. The site survey will be performed at NSWC facilities, Crane, Indiana. Upon completion of the site survey, a site-survey report will be issued to the Navy. The report will detail the results of the site survey, providing comments on facility deficiencies, and making suggestions to correct identified facility deficiencies.

1.1 Required Personnel

A ManTech site-survey team, in conjunction with Navy personnel, will be performing the site survey. We anticipate that the ManTech site-survey team will include a systems administration specialist, a hardware specialist, and a software specialist. We request that Navy personnel be present during the site-survey to provide assistance in gaining access to facility areas where the ASCAN hardware will be installed, and answer site-survey team members' questions. We recommend that Navy personnel familiar with the ASCAN system participate in the site survey.

1.2 Site-Survey Agenda

The site survey is tentatively scheduled to take place at NSWC facilities October 5-8, 1993. The site-survey report is tentatively scheduled for delivery on October 20, 1993. A pre-site-survey interview will be held prior to performing the site survey. The purpose of this interview is

- To introduce site-survey personnel.
- To discuss site-survey objectives.
- To provide a forum for questions/answers.

Following the site survey, ManTech personnel will be available to debrief Navy personnel on site-survey findings.

2 ASCAN SYSTEM REQUIREMENTS

The ASCAN software will be provided on 5.25-in. diskettes. This medium will contain all the source code and make files required to compile the system executables. The following hardware is required to install, compile, and operate this system:

- 586/66 MHz personal computer (PC).
- 32 MB random access memory (RAM).
- 1.05 GB on-line storage.
- 5.25-in. floppy diskette drive.
- Ethernet adaptor card.
- 20-in. monitor and graphics adapter (capable of 1280x1024 resolution).
- One open ISA card slot.

Computers using the ASCAN software should be loaded with the following system software:

- Microsoft MS-DOS (Version 5.0 or higher).
- Microsoft Windows Version 3.1
- Windows graphics drivers appropriate for the installed graphics board.
- Network software appropriate to the local area network (LAN) installed at NSWC.
- Microsoft Word for Windows Version 2.0 or higher (optional).
- Microsoft Help compiler (optional).
- Borland C++ Version 3.1 (optional).

A properly configured PC must be attached, and have access to the NSWC LAN. ManTech personnel will be available to answer any questions the Navy may have concerning proper PC configuration.

3 GOVERNMENT-FURNISHED EQUIPMENT GENERAL REQUIREMENTS

The VISUS high-resolution and Eagle 4080ET scanners require stable, vibration-resistant locations. The following list identifies equipment requiring BNC/Thin Ethernet LAN connections:

- VISUS high-resolution scanner.
- Intergraph 6700 server/workstation.
- Apollo workstations.
- PC scanner controller.
- Large-format binary convolver.

3.1 Space Requirements

The floor or counter space required for installation of GFE that will be returned to the Government prior to project completion is given below:

<u>Item</u>	Quantity	Length	<u>Width</u>	<u>Height</u>
Floor Items:				
VISUS high-resolution scanner.	1	72.0 in.	48.0 in.	56.0 in.
Intergraph 6700 server/workstation	1	16.0 in.	11.5 in.	25.5 in.
Eagle 4080ET drawing scanner	1	26.0 in.	58.0 in.	39.0 in.
<u>Item</u>	Quantity	Length	Width	<u>Height</u>
Counter Items:				
Apollo workstations	3			
Central processing unit (CPU)		17.5 in.	21.0 in.	7.0 in.
Monitor		17.0 in.	15.5 in.	17.0 in.
Keyboard		7.5 in.	20.5 in.	1.5 in.
Intergraph	1			
Monitor		20.0 in.	11.5 in.	25.5 in.
Keyboard		7.0 in.	17.5 in.	5.0 in.
Tape drive		11.5 in.	10.0 in.	5.0 in.
PC scanner controller	1			
CPU		16.5 in.	21.0 in.	6.5 in.
Monitor		12.5 in.	15.0 in.	11.0 in.
Keyboard		8.0 in.	18.5 in.	2.0 in.
Ricoh B-Size scanner	1	27.0 in.	48.0 in.	15.0 in.
Large-format binary convolver	1	16.5 in.	21.0 in.	6.5 in.
VISUS high-resolution-scanner accessories				
Monitor	1	15.0 in.	14.0 in.	16.0 in.
Keyboard	1	4.5 in.	8.0 in.	2.0 in.

3.2 Electrical Requirements

GFE equipment requiring connection to a 120-VAC, 60-Hz power source with approximately 20-amp capacity per connection is listed below:

<u>Item</u>	Number of Connections
Intergraph 6700	1
Eagle 4080ET scanner	1
VISUS high-resolution scanner	2
Apollo workstations	6
Ricoh scanner	. 1
PC scanner controller	2
Large-format binary convolver	1

4 ENVIRONMENTAL REQUIREMENTS

ASCAN equipment is affected by heat and humidity. The work space(s) allocated for this equipment requires air conditioning and heating that provide an environment within the following parameters:

Temperature:

50 to 80 degrees Fahrenheit

Relative Humidity:

40 to 80%

5 SITE-SURVEY CHECKLIST

The following checklist will be used by ManTech site-survey team personnel as a guide to evaluate NSWC facilities. The completed site-survey checklist will be attached and submitted as part of the site-survey report.

SITE-SURVEY CHECKLIST

Site Location:		Survey Date:	
----------------	--	--------------	--

Items Being Inspected	Quantity/ Parameters	Satisfactory	Unsatisfactory
Floor Space Requirements:	Latameters	Buttiffeed	Chautatetory
VISUS high-resolution scanner			
72in. x 48in. x 56in.	1		
Intergraph 6700 server			
16in. x 11.5in. x 25.5in.	1		
Eagle 4080ET drawing scanner			
26in. x 58in. x 39in.	1		
Counter Space Requirements:			
Apollo work stations:	3		
CPU 17.5in. x 21.0in. x 7in.			
Monitor 17in. x 15.5in. x 5in.			
Keyboard 7.5in. x 20.5in. x 1.5in.			
Intergraph:	1		
Monitor 20in. x 11.5in. x 25.5in.			
Keyboard 7.0in. x 17.5in. x 5in.			·
Tape drive 11.5in. x 10in. x 5in.			
PC scanner controller:	1		
CPU 16.5in. x 21in. x 6.5in.			
Monitor 12.5in. x 15in. x 11in.			
Keyboard 8in. x 18.5in. x 2in.			
Ricoh B-Size scanner	1		
27in. x 48in. x 15in.			
Large-format binary convolver	1		
16.5in. x 21in. x 6.5in.	·		
VISUS scanner accessories:			
Monitor 15in. x 14in. x 16in.	1		
Keyboard 4.5in. x 8in. x 2in.	1		
Electrical Requirements:			
120-VAC, 60-Hz,			
20-amp capacity	14		
Environmental Requirements:			
Temperature	50-80°F		
Humidity	40 - 80%		
Flooring Stability			

Items Being Inspected	Quantity of Items	Satisfactory	Unsatisfactory
Minimum Hardware Requirements:			
586/66 MHz PC	1		
32 MB. RAM	1		
1.05 GB On-line Storage	1		
5.25-in. floppy diskette drive	1		
Ethernet adapter card	1		·
20-in. monitor and graphics adapter (1280			
x 1024 resolution)	1		
Open ISA card slot	1		
Minimum Software Requirements:			
Microsoft MS-DOS (Ver. 5.0 or newer)	1		
Microsoft Windows v3.1	1		
Microsoft Word for Windows (Ver. 2.0 or			
newer)	1		
Microsoft Help compiler	1		
Borland C++ v3.1	1		
Windows graphics drivers	1		
Network software (LAN)	1		

Site-Survey Team members:

ManTech members:	Government members:			